



Klober's Trapac® Walkway allows work to be carried out more safely on the roof. Available in 4 colours to blend in with the roof, it suits concrete, clay, slate or fibre cement roofs.

Installation

Walkway should not exceed edge of Support Bracket by more than 10cm. To fit Walkway to Support Bracket two fixings per Support are required. The Support Brackets allow for 3 degrees of horizontal adjustment.

Profiled Tiles with load-bearing battens: Support Bracket is hung onto load-bearing batten. Additional battens are not required. With large format clay tiles an additional batten may be necessary if the distance between the battens is greater than 37cm.

Flat Tiles: For flat tiles an additional batten is required so that the Support Bracket can be secured through three holes in the metal strip. Maximum distance between Support Brackets is 90cm.

Product codes

| | |
|---|--------|
| 42cm | KS9130 |
| 60cm | KS9131 |
| 84cm | KS9132 |
| 102cm | KS9133 |
| 120cm | KS9134 |
| 150cm | KS9135 |
| 204cm | KS9136 |
| 252cm | KS9137 |
| 300cm | KS9138 |
| Connector | KS9140 |
| Support bracket clay/concrete | KS9120 |
| Support bracket slate/flat/ fibre cement | KS9121 |
| Fixings | KS9141 |

Related products

- Trapac® Safety Step
- Trapac® Tile & Snow Guard
- Trapac® Safety Hook

Product features & benefits

- Allows work to be carried out on the roof more safely, giving access to large areas of the roof
- 9 lengths available
- Lengths can easily be joined together using Connectors
- Available in 4 colours to blend in with the roof
- Universal for all roof types
- Solid and safe
- Adjustable for roof pitches
- Support brackets are adjustable in height & length for use with different profiles

Area of application

Suitable for:

- different tile profiles
- concrete, clay, slate & fibre cement
- different roof pitches using adjustable Support Bracket: clay/concrete: 20-56°, slate: 22-66°, flat/fibre cement: 19-58°

Material Walkway

Galvanised steel DX52 D+AZ 150 NA-C, powder coated

Connectors & Support Brackets

Galvanised steel DX51D/S235 JRG2 to EN1461

Fixings for Walkway to Support Bracket

Galvanised steel

Colours

Black
Dark brown
Galvanised
Terracotta

Dimensions

Please contact our Sales Office for details on dimensions

Weight

Please contact our Sales Office for details on weights

Packaging

Connectors 1 bag contains 2 connectors, 8 screws, washers and nut bolts

Fixings for Walkway to Support Bracket 1 bag consists of 48 fixings of screws, washers & nut bolts

Support bracket

10 pcs per carton